



HEAVY DUTY ANTIFREEZE/COOLANT

ANYWHERE. ANYTIME. ANY ENGINE.™

Prestone Command®

Heavy Duty Prediluted 50/50 Antifreeze/Coolant



Prestone Command® Heavy Duty Prediluted 50/50 Antifreeze/Coolant is a blend of antifreeze/coolant and demineralized water designed for use in ANY Heavy Duty Engines used in normal to severe duty cycles and extreme temperature conditions. This product will provide complete protection against freezing, overheating, cavitation erosion, corrosion, scale and foaming with just an easy pour and does not require SCAs in the initial fill. For flush and fill use Prestone Command® Heavy Duty concentrate.

WITH EXTENDED SERVICE INTERVAL TECHNOLOGY

SCA PRE-CHARGED

- Advanced corrosion protection technology
- For ANY heavy duty engine
- Compatible with ANY conventional heavy duty coolants and ALL filter technologies

Specifications and Performance: Prestone Command® Heavy Duty Prediluted 50/50 Antifreeze/Coolant meets or exceeds performance requirements of the major engine manufacturers and the following specifications: TMC RP-329, ASTM D-6210, ASTM D-4985, ASTM D-3306, SAE J1941

Stock #	UPC Code	Size
AFC10100	797496877697	1 gal.
AFC10100-55	797496877703	55 gal. drum
AFC10100-1KL	797496877741	264 gal.

Questions/Comments go to www.prestonecommand.com or call (888) 282-8960.

Reference recycle information from label.

Made in U.S.A.

© Property of Prestone Products Corporation
PRESTONE PRODUCTS CORPORATION, 1900 West Field Court, Lake Forest, IL 60045
©2013 Prestone Products Corporation



HEAVY DUTY ANTIFREEZE/COOLANT

ANYWHERE. ANYTIME. ANY ENGINE.™

PRESTONE COMMAND® HEAVY DUTY PREDILUTED 50/50 ANTIFREEZE/COOLANT

FEATURES & BENEFITS

- Low Silicate
- Requires No Initial Supplemental Coolant Additive (SCA)
- Very Low Dissolved Solids
- State-of-the-Art Scale Preventing Additives
- No Phosphates
- Blended with Demineralized Water
- Universal Formula: Heavy Duty and Industrial Applications

APPLICATION

A 50/50 mix of Prestone® Heavy Duty Antifreeze/Coolant will assure proper freeze protection/boilover protection and insure the proper concentration level of inhibitor is being provided. There is no need to use an initial charge of supplemental coolant additive or pre-charge spin on filter. Can be used with or without controlled release filter technology.

- DO NOT ADD WATER - For flush and fill use Prestone Command® ESI Concentrate product

GENERAL DESCRIPTION

Composition	Typical Values
Total Water	49%
Total Antifreeze	51%
Color	Purple
Odor	Not Offensive
Pack/Unit	Bulk/Drums/Gal. jugs
Fluid weight/unit	8.8 - 8.9 lb./gal.

Protection	Freeze-Up Protection	Boilover Protection†	Corrosion Protection
Prestone Command® HD Prediluted 50/50	-34°F (-37°C)	265°F (129°C)	Meets or exceeds ASTM D3306, ASTM D4985 and ASTM D6210

† Using a 15 lb. pressure cap in good condition.

Properties	Typical Values	ASTM Tests
Specific Gravity at 60°F (16°C)	1.075	D 1122
Boiling Point	227°F (108°C)	D 1120
Ash, Mass, %	0.3	D 1119
Foam Test	65 ml/2 sec.	D 1881
pH 50/50 Vol. Solution	10.4	D 1287
Freeze Point, 50/50 Solution	-34°F (-37°C)	D 1177
Total Dissolved Solids	0.3%	Federal # 209B

HANDLING

Keep container closed. In case of spill, clean up quickly as product is slippery. Flush small spills with water. Large spills, collect into drums for proper disposal. Dispose of or recycle according to federal, state or local regulations.

DOSAGE

For outstanding protection against freezing or boil-over use the 50/50 Prediluted Prestone® without further dilution. Concentration levels should not fall below 50% by volume.

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF THE FOLLOWING SPECIFICATIONS*

Heavy Duty

- ASTM D-4985 & D-6210
- Case Corp. MS1710
- Caterpillar Heavy Duty Coolant
- CID A-A-52624A
- Cummins CES 90T8-4 and 14603
- Detroit Diesel 7SE298 and 93K217
- EMD M.I.1748E
- Ford New Holland 9-86
- Freightliner 48-22880
- GM 1899M and GM 6038M
- John Deere H24A1 & 8650-5
- Kenworth R026-170-97
- Mack
- PACCAR
- Navistar B-1
- Peterbilt 07-06773
- SAE J1941
- Thermo-King
- TMC RP-302A & RP-329
- Volvo GM
- Waukesha 4-1974D

Automobile

- ASTM D-3306
- ASTM D-4340
- Chrysler MS 7170 Section A & B 1-4
- CSMA
- Ford ESE-M97B44-A Section 3.1.1 & 3.1.2
- GM 1825M and GM 6043M
- SAE J1034

* For updated list of specifications, visit www.prestonecommand.com

Questions/Comments go to www.prestonecommand.com or call (888) 282-8960.

Reference recycle information from label.

Made in U.S.A.

© Property of Prestone Products Corporation
PRESTONE PRODUCTS CORPORATION, 1900 West Field Court, Lake Forest, IL 60045
©2013 Prestone Products Corporation